

CFZ- 20 Series

CFZ-20 high-end series and professional strong plastic structured models with axial fan, which need to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



APPLICATIONS:



Factories



Workshops



Entertainment Centers



Supermarkets & Malls



Prayer Halls & Schools

SPECIFICATIONS



Fully Automated Function



Self Cleaning Function



Reverse Air Supply Function



Digital Control Panel



100% Copper Wired Motor



UV Stabilized Engineering Plastic



Model

Model	CFZ-20A	CFZ-20B	CFZ-20C
Discharge Type	Bottom	Side	Top
Voltage/Frequency	220~240V/380~415V	220~240V/380~415V	220~240V/380~415V
Frequency	50~60 Hz	50~60 Hz	50~60 Hz
Max. Air Flow	20,000 m ³ /h	20,000 m ³ /h	20,000 m ³ /h
Working Current	4.8A/2.7A	4.8A/2.7A	4.8A/2.7A
Power Consumption	1.1 KW	1.1 KW	1.1 KW
Dimensions	1120*1120*1050mm	1120*1120*1050mm	1120*1120*1050mm
Air Outlet Size	670*670 mm	670*670 mm	730*730 mm
Net Weight	60 Kg	60 Kg	60 Kg
Water Tank Capacity	25 L	35 L	35 L
Water Consumption	65 L/h	65 L/h	65 L/h

DUCTED SERIES