

CFZ- 25/35/45/60BC Series

CFZ-25/35/45/60BC Series are popular stainless steel structured model, metal housing and powder coating surface treatment, robust and reliable. Centrifugal-type ventilation unit provides high hydrostatic pressure and long-distance fresh air delivery. Which needs to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



APPLICATIONS:

-  Factories
-  Workshops
-  Entertainment Centers
-  Supermarkets & Malls
-  Prayer Halls & Schools

SPECIFICATIONS

Model	CFZ-25BC	CFZ-35BC	CFZ-45BC	CFZ-60BC
Type	Centrifugal	Centrifugal	Centrifugal	Centrifugal
Voltage/Frequency	380~415V/50~60 Hz	380~415V/50~60 Hz	380~415V/50~60 Hz	380~415V/50~60 Hz
Max. Air Flow	25,000 m ³ /h	35,000 m ³ /h	45,000 m ³ /h	60,000 m ³ /h
Working Current	11.6 A	15.4 A	24.5 A	30.3 A
Power Consumption	5.5 KW	7.5 KW	11 KW	15.5 KW
Dimensions	1500*1580*1400mm	1770*1770*1440mm	2090*1970*1700mm	2090*1970*1700mm
Air Outlet Size	620*570mm	782*700mm	862*700mm	926*834mm
Net Weight	300 Kg	450 Kg	585 Kg	650 Kg
Water Tank Capacity	65 L	80 L	100 L	100 L
Water Consumption	117L/h	220L/h	260L/h	380L/h



Fully Automated Function



Self Cleaning Function



Reverse Air Supply Function



Digital Control Panel



100% Copper Wired Motor



UV Stabilized Engineering Plastic



DUCTED SERIES