

## CFZ- 25 Series

CFZ-25 high-end series and professional strong plastic structured models with axial fan, which need to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



### APPLICATIONS:



Factories



Workshops



Entertainment Centers



Supermarkets & Malls



Prayer Halls & Schools

## SPECIFICATIONS



Fully Automated Function



Self Cleaning Function



Reverse Air Supply Function



Digital Control Panel



100% Copper Wired Motor



UV Stabilized Engineering Plastic



### Model

### CFZ-25A

### CFZ-25C

Discharge Type

Bottom

Top

Voltage/Frequency 220~240V/380~415V/50~60 Hz 220~240V/380~415V/50~60 Hz

Max. Air Flow

25,000 m<sup>3</sup>/h

25,000 m<sup>3</sup>/h

Working Current

6.8 A/3.7 A

6.8 A/3.7 A

Power Consumption

1.5 KW

1.5 KW

Dimensions

1120\*1120\*1250 mm

1120\*1120\*1300 mm

Air Outlet Size

670\*670 mm

730\*730 mm

Net Weight

79 Kg

79 Kg

Water Tank Capacity

25 L

35 L

Water Consumption

75 L/h

75 L/h

## DUCTED SERIES