

CFZ- 30 Series



APPLICATIONS:

-  Factories
-  Workshops
-  Entertainment Centers
-  Supermarkets & Malls
-  Prayer Halls & Schools

CFZ-30 Series are popular stainless steel structured model, the chassis and top cover are made of stainless steel, and the pillars are made of Aluminum alloy, with powder coating surface treatment, robust and reliable. Axial-flow ventilation unit providing large airflow, which need to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.

-  Fully Automated Function
-  Self Cleaning Function
-  Reverse Air Supply Function
-  Digital Control Panel
-  100% Copper Wired Motor
-  UV Stabilized Engineering Plastic



SPECIFICATIONS

Model	CFZ-30A	CFZ-30B
Discharge Type	Bottom	Side
Voltage/Frequency	380~415V/50~60 Hz	380~415V/50~60 Hz
Max. Air Flow	30,000 m3/h	30,000 m3/h
Working Current	5.6A	5.6A
Power Consumption	2.2 KW	2.2 KW
Dimensions	1500*1500*1350 mm	1500*1580*1350 mm
Air Outlet Size	800*800 mm	800*800 mm
Net Weight	170 Kg	180 Kg
Water Tank Capacity	65 L	65 L
Water Consumption	117 L/h	117 L/h

DUCTED SERIES