

CFZ- 36 Series

CFZ-36 Series are popular stainless steel structured model, the chassis and top cover are made of stainless steel, the pillars are made of Aluminum alloy, with powder coating surface treatment, robust and reliable. Axial-flow ventilation unit provides large airflow, which needs to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



APPLICATIONS:

-  Factories
-  Workshops
-  Entertainment Centers
-  Supermarkets & Malls
-  Prayer Halls & Schools



Fully Automated Function



Self Cleaning Function



Reverse Air Supply Function



Digital Control Panel



100% Copper Wired Motor



UV Stabilized Engineering Plastic



SPECIFICATIONS

Model	CFZ-36A	CFZ-36B
Discharge Type	Bottom	Side
Voltage/Frequency	380~415V/50~60 Hz	380~415V/50~60 Hz
Max. Air Flow	36,000 m3/h	36,000 m3/h
Working Current	6.5 A	6.5 A
Power Consumption	3.0 KW	3.0 KW
Dimensions	1500*1500*1350mm	1500*1580*1350mm
Air Outlet Size	800*800 mm	800*800 mm
Net Weight	175 Kg	185 Kg
Water Tank Capacity	65 L	65 L
Water Consumption	150 L/h	150 L/h

DUCTED SERIES